

Schnellspanner horizontal mit waagrechttem Fuß und verstellbarer Andruckspindel

Art. Nr.	Material Grundkörper	Öffnungswinkel			Handkraft FH N	Haltekraft F1 N	Haltekraft F2 N	Spannkraft F3 N	Spannkraft F4 N	passender Kunststoffgriff
		Haltearm	Griff							
101 130 468	Stahl	90°	75°	80	500	1100	250	700	K0100.16	
101 130 469	Stahl	90°	80°	140	1200	2600	400	1000	K0100.20	
101 130 470	Stahl	95°	80°	200	1500	3500	800	1950	K0100.28	
101 130 471	Stahl	90°	75°	250	2500	5500	1150	3100	K0100.30	
101 130 472	Stahl	90°	75°	250	3000	6500	1150	3100	K0100.34	

Art. Nr.	Material Grundkörper	Abmessungen														
		A	A1	A2	B	B1	B2	B3	B4	C	C1	D	H	L	L1	M
101 130 468	Stahl	13,5	25	5,7	17,4	27	16	5,8	-	19	9,5	5,2	38	116	37	M5x35
101 130 469	Stahl	26	38	6	28	40	20	6,2	22	24	14	5,5	53	170	60	M6x50
101 130 470	Stahl	26	42	8	31	47	23	8,5	26	35	17,5	6,6	68	224	79	M8x60
101 130 471	Stahl	41,2	59	9	43	59	30	12	39	45	24	8,7	91	274	108	M10x80
101 130 472	Stahl	41,2	67	13	41,3	67	38	14,2	-	59	27	8,7	110	305	128	M12x100