Page 1 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001

Valid from: 03.08.2015 PDF print date: 03.08.2015 à^\[Â\Jāak] Áx&^cæc

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

VY_c'G]`]Wcb'UWYhUh

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Silicone sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

(GB)

à^\[ÁÕ{àPÉÄÜæ}]^}-^|å•dÉÁÉÖÒÉÎÎÎÍHÁT[}@?ã Ú@}^ÆÍJÁŒÐÁSJFËJÐÌÌËÐÉØæ¢ÆÍJÁŒÐÁSJFËJÐÌÌËGJ

Qualified person's e-mail address: 3 { O à^\[E |[] E [{

1.4 Emergency telephone number

Emergency information services / official advisory body:

Poison Control Center Mainz - 24 hour emergency service

phone: +49 (0) 6131/19240

Telephone number of the company in case of emergencies:

Phone: +49 (0) 9091-90898-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

Page 2 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001

Valid from: 03.08.2015 PDF print date: 03.08.2015 à^\[ÂÛãã8[} Áæ&^ææ

3.2 Mixture

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	
Registration number (REACH)	01-2119827000-58-XXXX
Index	
EINECS, ELINCS, NLP	934-956-3 (REACH-IT List-No.)
CAS	
content %	20-30
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Ethyltriacetoxysilane	
Registration number (REACH)	01-2119881778-15-XXXX
Index	
EINECS, ELINCS, NLP	241-677-4
CAS	17689-77-9
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Skin Corr. 1B, H314

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Formaldehyde

Page 3 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001

Valid from: 03.08.2015 PDF print date: 03.08.2015 à^\[ÂJāã[] Áæ&^æe

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Flush residue using copious water.

Or:

Allow product to harden.

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3

Page 4 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001

Valid from: 03.08.2015 PDF print date: 03.08.2015 à^\[ÂÛ4a8[} Áx&^cæc

[®] Ch	nemical Name	Hydrocarbons	itics	Content %:20- 30		
	TWA: 1200 mg/m3 (>= C7 ned chain alkanes)	normal and		WEL-STEL:		
	oring procedures:	_	D	raeger - Hydrocarbons 2/a (81 03 581)		
	5 .	-	D	raeger - Hydrocarbons 0,1%/c (81 03 571)		
		-	С	ompur - KITA-187 S (551 174)		
BMGV	/:			Other information:		

© Chemical Name	Silica, amorphous	3		Content %:
WEL-TWA: 6 mg/m3 (total inh.	dust), 2,4 mg/m3	WEL-STEL:		
(resp. dust)				
Monitoring procedures:	=			
BMGV:			Other information: -	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Silica, amorphous						
Area of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental compartment		r			
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Safety gloves made of chloroprene (EN 374).

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Page 5 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001

Valid from: 03.08.2015 PDF print date: 03.08.2015 à^\[ÁÛãã&[}Áæ&^cæc

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Solid, Pastelike

Colour: According to specification

Odour: Acetic acid Odour threshold: Not determined

pH-value: <7 <-40 °C Melting point/freezing point: Initial boiling point and boiling range: n.a

Flash point: Not determined Evaporation rate: Not determined Flammability (solid, gas): >440 °C Lower explosive limit: n.a.

Upper explosive limit:

Vapour pressure: Not determined Vapour density (air = 1): n.a.

Density: 0,98-1,00 g/cm3 Bulk density: n.a.

Not determined Solubility(ies): Water solubility: Insoluble

Partition coefficient (n-octanol/water): Not determined Not determined Auto-ignition temperature: Decomposition temperature: Not determined Viscosity: >20,5 mm2/s

Explosive properties: Nο Oxidising properties: No

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Surface tension: Not determined Solvents content:

SECTION 10: Stability and reactivity

10.1 Reactivity

Page 6 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001

Valid from: 03.08.2015 PDF print date: 03.08.2015 à^\[ÂÛ4æ}[} Áæ&^æe

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Strong heat

Moisture

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
	nt					
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification accordi
						to calculation
						procedure.

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics											
Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes					
	nt										
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute						
					Oral Toxicity)						
Acute toxicity, by dermal	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute	24h					
route:					Dermal Toxicity)						
Acute toxicity, by inhalation:	LC50	>5266	mg/m3/	Rat	OECD 403 (Acute	Aerosol					
			4h		Inhalation Toxicity)						
Skin corrosion/irritation:					OECD 404 (Acute	Not irritant					
					Dermal						
					Irritation/Corrosion)						

Page 7 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001 Valid from: 03.08.2015

PDF print date: 03.08.2015 à^\ [ÂJāã[] Ásã^cæc

Serious eye damage/irritation:		OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Germ cell mutagenicity:			Negative
Reproductive toxicity:			Negative
Aspiration hazard:			Yes
Symptoms:			vomiting, skin afflictions

Toxicity / effect	Endpoi	Value	Unit	Organism	Test method	Notes
•	nt					
Acute toxicity, by oral route:	LD50	1460	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit		Corrosive
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Classification based on
					Irritation/Corrosion)	toxicological
					ŕ	analyses.<5%
Serious eye				Rabbit	OECD 405 (Acute	Not irritant,
damage/irritation:					Eye	Classification based on
•					Irritation/Corrosion)	toxicological
					ŕ	analyses.<5%
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	,
Symptoms:					,	mucous membrane irritation

Silica, amorphous						
Toxicity / effect	Endpoi nt	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit		Not irritant, References
Serious eye damage/irritation:				Rabbit		Not irritant, Mechanical irritation possible., References
Respiratory or skin sensitisation:				Guinea pig		Not sensitizising
Symptoms:						eyes, reddened

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Silikon-Dichtstoff SE1	Silikon-Dichtstoff SE130 ungefüllt												
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes						
Toxicity to fish:							n.d.a.						
Toxicity to daphnia:							n.d.a.						
Toxicity to algae:							n.d.a.						
Persistence and							n.d.a.						
degradability:													
Bioaccumulative							n.d.a.						
potential:													
Mobility in soil:							n.d.a.						
Results of PBT and							n.d.a.						
vPvB assessment													
Other adverse effects:							n.d.a.						

Page 8 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001 Valid from: 03.08.2015

Valid from: 03.08.2015 PDF print date: 03.08.2015 à^\ [ÂJāã[} Áæ&^ææ

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LL50	96h	>1028	mg/l	Scophthalmus	OECD 203	
					maximus	(Fish, Acute	
						Toxicity Test)	
Toxicity to daphnia:	LL50	48h	>3193	mg/l	Acartia tonsa	ISO 14669	
Toxicity to algae:	ErL50	72h	>1000	mg/l	Skeletonema	ISO 10253	
			0		costatum		
Persistence and		28d	74	%		OECD 306	Readily biodegradable
degradability:						(Biodegradabilit	
						y in Seawater)	
Persistence and		28d	74	%		OECD 306	Readily biodegradable
degradability:						(Biodegradabilit	
						y in Seawater)	
Bioaccumulative							Yes
potential:							
Mobility in soil:							Not to be expected
Results of PBT and							No PBT substance, No
vPvB assessment							vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	251	mg/l	Brachydanio rerio		
Toxicity to daphnia:	EC50	48h	62	mg/l	Daphnia magna		
Toxicity to algae:	IC50	72h	73	mg/l	Scenedesmus subspicatus		
Persistence and degradability:		21d	74	%	·	Regulation (EC) 440/2008 C.4-A (DETERMINATI ON OF 'READY' BIODEGRADA BILITY - DOC DIE-AWAY TEST)	

Silica, amorphous									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203			
			0			(Fish, Acute			
						Toxicity Test)			
Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202			
			0			(Daphnia sp.			
						Acute			
						Immobilisation			
						Test)			
Toxicity to algae:	EL50	72h	>1000	mg/l		OECD 201			
			0			(Alga, Growth			
						Inhibition Test)			
Persistence and							Abiotically degradable.		
degradability:									
Results of PBT and							No PBT substance, No		
vPvB assessment							vPvB substance		

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

Page 9 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001

Valid from: 03.08.2015 PDF print date: 03.08.2015 à^\[ÂJāã[] Áæ&^æe

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 02 17 waste containing silicones other than those mentioned in 07 02 16

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

Hardened product:

Can be disposed of with household rubbish.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 02 plastic packaging

SECTION 14: Transport information

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es):

Packing group:

Classification code:

LQ (ADR 2015):

n.a.

n.a.

Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:

Transport hazard class(es):

Packing group:

Marine Pollutant:

n.a.

Environmental hazards: Not applicable

Transport by air (IATA)

UN proper shipping name:

Transport hazard class(es): n.a. Packing group: n.a. n.a.

Environmental hazards: Not applicable

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable. Directive 2010/75/EU (VOC): 0 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Page 10 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001

Valid from: 03.08.2015 PDF print date: 03.08.2015 à^\[Â\Jā̃ãš[} Áæš^cæc

Revised sections:

1-16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

Asp. Tox. — Aspiration hazard Acute Tox. — Acute toxicity - oral Skin Corr. — Skin corrosion

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIHAmerican Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

Page 11 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001

Valid from: 03.08.2015 PDF print date: 03.08.2015 à^\[Â\Jā̄æ \^cæc

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLIDInternational Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAELLowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSHNational Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

Page 12 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 03.08.2015 / 0002

Replacing version dated / version: 21.01.2015 / 0001

Valid from: 03.08.2015 PDF print date: 03.08.2015 à^\[Â\Jā̃ãš[} Áæš^cæc

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.