



RAMPA®-Muffen Typ SK
mit Innensechskant, vereinfachtes Einschrauben durch Führungsansatz

RAMPA®-inserts type SK
with hex socket drive, an unthreaded lead supports easy assembly

SK

Art.	D	L	d	SW HD	Vorbohrung Pilot hole	Stahl verzinkt Steel zinc plated	Messing blank Brass plain	Stahl rostfrei Stainless steel 1.4305	Stahl rostfrei Stainless steel 1.4571
010 408	8	8	M 4	4	7,0 – 7,5	•		•	•
010 410	8	10	M 4	4	7,0 – 7,5	•	•		•
010 412	8	12	M 4	4	7,0 – 7,5	•			
010 508	10	8	M 5	5	8,0 – 8,5	•			
010 510	10	10	M 5	5	8,0 – 8,5	•			
010 512	10	12	M 5	5	8,0 – 8,5	•	•	•	
010 514	10	14	M 5	5	8,0 – 8,5	•			•
010 610	12	10	M 6	6	10,0 – 10,5	•			
010 612	12	12	M 6	6	10,0 – 10,5	•		•	
010 615	12	15	M 6	6	10,0 – 10,5	•	•	•	•
010 618	12	18	M 6	6	10,0 – 10,5	•			•
010 620	12	20	M 6	6	10,0 – 10,5	•			
010 623	12	23	M 6	6	10,0 – 10,5	•			
010 625	12	25	M 6	6	10,0 – 10,5	•			
010 852	14	12	M 8	8	12,0 – 12,5	•			
010 855	14	15	M 8	8	12,0 – 12,5	•			
010 858	14	18	M 8	8	12,0 – 12,5	•			
010 870	14	30	M 8	8	12,0 – 12,5	•			
010 814	16	14	M 8	8	14,0 – 14,5	•			
010 818	16	18	M 8	8	14,0 – 14,5	•	•	•	•
010 823	16	23	M 8	8	14,0 – 14,5	•			
010 830	16	30	M 8	8	14,0 – 14,5	•			•
010 115	18,5	15	M 10	10	16,0 – 16,5	•			
010 120	18,5	20	M 10	10	16,0 – 16,5	•			
010 125	18,5	25	M 10	10	16,0 – 16,5	•	•		
010 130	18,5	30	M 10	10	16,0 – 16,5	•			
010 140	18,5	40	M 10	10	16,0 – 16,5	•			
010 230	22	30	M 12	12	20,0	•			
010 240	22	40	M 12	12	20,0	•			

↑ Bitte ergänzen / Please complete

001	01	03	07
-----	----	----	----